

Stackable High Voltage Lithium Battery

SAS51280-HV

51.2V 280Ah

LFP Battery



PRODUCT FEATURE



HIGH CYCLE LIFE

Can achieve 6000 cycles at 90% state of charge, effectively reducing total cost of ownership.



FAST CHARGING SPEED

High charge and discharge efficiency, reducing equipment downtime and saving more time.



HIGHLY ADAPTABLE

Strong environmental adaptability, can withstand up to 60°C.



SAFER

Real-time monitoring of PDU for better system protection.



EASY TO STORE

Due to its extremely low self-discharge rate (LSD) and no risk of sulfation, it can last up to 6 months.



EASY TO STORE

Lithium batteries provide more watt-hours per kilogram while weighing only one-third of their SLA equivalents.



Email: info@sailsolarpv.com Web: www.sailsolarpv.com www.sailsolares.com
Add: Cross Border E-Commerce Supervision Zone, Yulei Road, Hefei, Anhui, China

HIGH VOLTAGE LITHIUM BATTERY

DATASHEET

MODEL

Battery Type	LiFePO4				
Nominal Battery Energy	14.336kWh				
Nominal Capacity	280Ah				
Nominal Voltage	51.2V				
Net Weight	115.2kg				
Dimension(W/D/H)	798*478*278mm				
Communication	RS232/RS485/CAN/BLUETOOTH/WIFI				
Cycle Life*	6000 cycles 80% DOD,0.5C				
Protection Level	IP20				
Expansion	Up to 15 units in series				
Compatible Inverters	Deye/GoodWe/Solis/SAJ/Sinexcel/Hoymiles/Growatt/Ecatus/Sermatec/ATESS/Sunways etc.				
Certification & Safety Standard	UN38.3, MSDS, IEC62619, CE, UL1973, UL2054				
Stackable Type	SAS-157.6KWH-Z	SAS-172KWH-Z	SAS-186.3KWH-Z	SAS-200.7KWH-Z	SAS-215.04KWH-Z
Battery Module Quantity	11units	12units	13units	14units	15units
Nominal Battery Energy	157.6kWh	172kWh	186.3kWh	200.7kWh	215.04kWh
Nominal Capacity	280Ah	280Ah	280Ah	280Ah	280Ah
Nominal Voltage	563.2V	614.4V	665.6V	716.8V	768V
Max.Power Output	157.6kW	172kW	186.3kW	200.7kW	215.04kW
Discharge Cut-off Voltage	484V	528V	572V	616V	660V
Charge Cut-off Voltage	624.8V	681.6V	738.4V	795.2V	852V
Recommend Charging Current	100A	100A	100A	100A	100A
Recommend Discharging Current	100A	100A	100A	100A	100A
Max Charge/Disharge Working Current (A)	200A	200A	200A	200A	200A
Net Weight	1,267.2KG	1,382.4KG	1,497.6KG	1,612.8KG	1,728KG
Working temperature	Charge : 0 ~ 55°C / Discharge : -20°C ~ 55°C				
Design Life	10 years+				

*File version: 2026V1-EN

*Weight and Size of the battery module is based on the actual product,

*Specifications may vary during continuous improvements, pls contactus for latest details.

*The installation of battery packs is related to product quality assurance, safe and stable operation. Please follow the requirements of the user manual for standardized installation, use, and routine maintenance

*Each column can hold a maximum of 5 batteries plus one high-voltage box, please confirm the number of batteries per column with the sales team



Email: info@sailsolarpv.com Web: www.sailsolarpv.com

Add: Cross Border E-Commerce Supervision Zone, Yulei Road, Hefei, Anhui, China

