

# **Lithium Battery**

51.2V 280AH 14336wh

#### · Safety and Intelligent

Long life LiFePO4 cells, high energy density, build in BMS and passive protection

#### · Easy to Install and Use

Modular design, simple operation

#### · Long Life Span

10 years design life, more than 6000cycles

## • Adaptable to Harsh Environment Adapt to wide range of temperature and humidity

### · Support Bluetooth/WIFI function (optional)

Can be controlled remotely to reduce operation and maintenance costs

• Multi-scenario application

Household use, small industrial and commercial applications



## **Technical Parameters**

Nominal voltage	51.2V
Nominal capacity	280Ah
Energy	14336wh
Interal Resistance	≤200mΩ
Cycle Life	>6000 cycles @ 0.2C 80%D.O.D
Months Self Discharge	<3%
Efficiency of Charge	99.5%@ 0.20
Effciency of Discharge	96-99%@ 10
Charge Voltage	58.4±0.5V
Charge Mode	cc/cv
Charger Current	40A
Max Charge Current	200A
Charge Cut-off Voltage	58.4
Continuous discharge Current	40A
max discharge Current	200A
Discharge Cut-off Voltage	43.2V
Charge Temperature	0 ℃ to 45 ℃
Discharge Temperature	-20 ℃ to 55 ℃
Storage Temperature	-10 °C to 40 °C
Water Dust Resistance	IP20
Cell & Method	EVE 3.2V280Ah-16S1
Terminal	200A
Protocol (optional)	RS232/RS485/CAN/BLUETOOTH/WIFI
BMS	200A
Safety & Certification	CELL:UL1642/UL1973/IEC62619/CE/CB/UN38.3/UL9540/ROHS/REACH
Size (mm)	772*460*237(D*W*H)
Net weight (kg)	114KG
Wooden box package size (mm)	940*555*405
Quantity of loading	120pcs/20ft 240pcs/40ft

## **Notes**

- \*1 Test conditions: Based on the factory date, charge and discharge rate at 0.2C at 100% discharge depth (DoD) and 25
- \*2 The weight of the battery module is based on the actual product, with a tolerance of ± 3% allowed
- \*3 The installation of battery packs is related to product quality assurance, safe and stable operation. Please follow the requirements of the user manual for standardized installation, use, and routine maintenance

## **Compatibility Inverters**

















<sup>\*</sup>Only a part of inverter brands are shown, please contact us for more information.

